

INTER-TREATMENT DEGREASING AND PASSIVATING AGENT FOR SPRAY WASHING MACHINES

Approvals and conformities

SNECMA	DMP 12-300 & 13-300 ; DMR 70-700
TURBOMECA	CCT LB 540
SNCF (French Railways)	Symbole 02107916

COMORAL DSP is intended for degreasing metallic parts, aluminium alloys, steel, stainless steel or cast iron. COMORAL DSP has exceptional properties. It is the reference product for mechanical industries.

COMORAL DSP is a passivating-neutralizing agent. Its passivating properties on metals restore tanks and circulation pipes after scale removal (COMOROX DTL).

- SAFETY: COMORAL DSP is free from nitrites (toxic) soda, potash (corrosive), solvents (flammable). Effluent discharge is made easier.
- SAVING: COMORAL DSP can be used at low temperature (30 to 50° C) low concentration (2 to 4 % on average). It protects parts stored under cover without requiring any subsequent treatment or rinsing.
- QUALITY: COMORAL DSP is biodegradable. It is completely miscible with water. It contains surfactants necessary for optimum degreasing. It can be used safely before and after heat treatment.
- EASY TO USE: COMORAL DSP is a low foaming product. 2 to 5 minutes contact time is necessary to obtain a good result. The salting-out power of oils gives easy cleaning of trays and machine tanks ; the bath can be easily controlled by a quick dosage..

DIRECTIONS FOR USE

- The application concentration depends upon the amount of soils and greases to be removed from the parts. In most cases maintain the temperature between 40 and 50°C, concentration 3 %, contact time 4 to 5 minutes.
- As a passivating-neutralizing agent: concentration 5%, contact 5 minutes.

TECHNICAL CHARACTERISTICS

Appearance clear liquid



Support technique International / International Technical Support
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomore.com
Pour connaître notre correspondant le plus proche / To find our nearest correspondent
socomore@socomore.com



Odour	low
Density	(at 20°C) 1
pH	(at 10%) 10
Flash point	(ISO 2719) none
Resistance to cold	homogeneous at -10°C
Free from	soda, phosphate, potash

PRECAUTIONS FOR USE AND STORAGE

As for any other degreasing alkaline product and if you are likely to be in contact with the product it is recommended to wear protection (gloves, aprons, etc...)

A slight deposit may appear during storage which does not affect the product quality.

Please read the safety data sheet for further information.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by Socomore ; all data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.



Support technique International / International Technical Support
 tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomore.com
 Pour connaître notre correspondant le plus proche / To find our nearest correspondent
 socomore@socomore.com

