

### Approvals and conformities

TURBOMECA

CCT LB 540

DGA (French Army)

Fiche d'identification n° 3735

- Excellent dissolving action on paints, inks (classical or UV), varnishes or adhesives.
- Compatibility with most synthetic resins (epoxy, polyurethane, acrylic...).
- Non-corrosive on metals and few losses by evaporation.
- Very safe due to the high flash point.
- The flash point is stable in time and remains constant throughout the evaporation duration.

### USES

---

- Solvent used for cleaning resin application equipment, as a replacement for acetone, MEK or toluene.
- Reactivating cleaning solvent for metallic or painted surfaces before painting.

### DIRECTIONS FOR USE

---

- DIESTONE A8287 is suitable for long term dipping or impregnating operations (removal of resins). It can also be applied by means of a brush or a swab.
- After cleaning, the application material must be dried thoroughly.

### TECHNICAL CHARACTERISTICS

---

Appearance .....	colourless clear liquid
Density .....	0.89
Flash point .....	(ISO 2592) 40°C
Evaporation rate (NFT 30301) .....	0.3

### PRECAUTIONS FOR USE AND STORAGE

---



Support technique International / International Technical Support  
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomore.com  
Pour connaître notre correspondant le plus proche / To find our nearest correspondent  
socomore@socomore.com

socomore  
finishing solutions

Because of the degreasing action of the product, it is advised to wear safety gloves during handling. As for all flammable solvents, take the usual safety measures during use and storage.

Please read the safety data sheet for further information.

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by Socomore ; all data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.



Support technique International / International Technical Support

tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomore.com

Pour connaître notre correspondant le plus proche / To find our nearest correspondent

socomore@socomore.com

**socomore**  
finishing solutions