

## WATER-SOLUBLE CLEANING DILUENT WITH A HIGH FLASH POINT

### Approvals and conformities

SNECMA

DMP 12-300 & 13-300 ; DMR 70-710

**DN 108 is a safe compound with a high flash point and a controlled volatility, free from harmful constituents, chlorinated or benzene hydrocarbons.**

- Excellent dissolving action on paints, inks (classic or U.V.), varnishes and adhesives Compatible with most synthetic resins (epoxies, polyurethanes, acrylics, etc ...)
- Non corrosive on metals
- Few losses by evaporation
- Very safe because of its high flash point
- Slight odour
- Perfectly water-soluble
- Biodegradability
- Recycling is possible by distillation.
- Easy salting-out of oils and smears in oil extractor
- The flash point is stable in time and remains constant throughout the evaporation duration.

### USES

---

DN 108 is suitable in workshops using paints, inks, varnishes and adhesives for:

- the cleaning of application materials (included for screen printing),
- the degreasing and cleaning of metallic parts composites (after checking of compatibility).

### DIRECTIONS FOR USE

---

DN 108 may be used pure or diluted.

- Use it pure in case of long time operations by dipping or impregnation (removing of resins). DN 108 may also be applied by brushing or with a rag.
- As an additive for degreasing in aqueous medium, DN 108 efficiently removes temporary protective inks and varnishes (such as PROPACO). It can also be used as a surface preparation before painting to remove dirt and



greasy marks. The product is to be incorporated into water at the rate of 3 to 10 % when working with a hot water machine under pressure, and at the rate of 30 to 50 % in case of cold using. (joints type "Viton" or "Teflon" advised)

## TECHNICAL CHARACTERISTICS

---

Appearance . . . . .	clear colourless liquid
Density . . . . .	(at 20°C/68°F) 0.94
Flammability point . . . . .	(ISO 2592) 56°C/132°F
Evaporation rate (NFT 30301) . . . . .	0.09
Water miscibility . . . . .	total
Viscosity cup 2.5 (NFT 30014) . . . . .	30 seconds

## PRECAUTIONS FOR USE AND STORAGE

---

Because of the powerful degreasing action of DN 108 on the skin, users are recommended to wear gloves. They must also avoid breathing or swallowing the product, and have to wear protective glasses to prevent splashing into eyes. In case of contact with the skin or the eyes, rinse immediately with plenty of water.

DN 108 must be used and stored far away from flames or heat sources, in well-ventilated rooms. During storage, keep it in the original closed package under shelter.

Please read the safety data sheet for further information.

**This technical data sheet replaces and cancels the previous one.**

The above details have been compiled to the best of our knowledge, they have, however, an indicative value only, and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by Socomore ; all data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact our services.



Support technique International / International Technical Support  
tel. +33 (0)2 97 43 76 90 fax +33 (0)2 97 54 50 26 E-mail Support@socomore.com  
Pour connaître notre correspondant le plus proche / To find our nearest correspondent  
socomore@socomore.com

