

Approvals and conformities

ASME
RCC-M
RSE-M
ISO 3452-5
PMUC (French acronym for : Products and Equipments allowed for use in Powerplants by EDF - French Electricity Bo
ISO 3452-2

MANUFACTURER : BABB CO (Fr)

DESCRIPTION / APPLICATION(S):

Remover designed to remove PRT23E high temperature penetrant from hot parts (120 to 200°C)
Companion product(s): Hi Temp penetrant: PRT23E
Hi Temp developer: RT71

DIRECTIONS FOR USE

First of all, eliminate most of the excess off PRT23E penetrant, by wiping the part with clean, dry cloths, then wipe with a clean cloth slightly moistened with NT101B, and wipe again with a clean dry cloth to eliminate the last traces of penetrant.

Do not spray directly NT101B on the part.

Apply immediately after a thin layer of RT71 (see technical data sheet)

TECHNICAL CHARACTERISTICS

Very low halogen and sulfur content.
Compatible with any metal.

Appearance colorless to yellowish liquid
Flash point between -18°C and 23°C

PRECAUTIONS FOR USE AND STORAGE

1 Date : 06-07-2017 Written and checked by : F. Héron

Shipping / Handling: refer to MSDS

Storage : keep away from moisture

Temperature limit: -5 to 50° C.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.