

## Approvals and conformities

PSA PEUGEOT CITROEN

Report 06-142 per B 74 2640

- Water-soluble phase.Reduces the coefficient of friction.
- Compatible with elastomers.
- Especially inhibited.Does not develop corrosion on steel, nor aluminium.
- Resistance to temperature: 0 to +60°C

## USES

Lubricant in aqueous phase used as slipping agent for elastomer, particularly adapted for mounting tires.

## DIRECTIONS FOR USE

The product is ready for use and does not require any dilution.

## TECHNICAL CHARACTERISTICS

Composition ..... surfactants, soaps, corrosion inhibitors  
Appearance ..... bleu viscous liquid  
pH ..... (undiluted) 9  
Specific gravity ..... 1

## PRECAUTIONS FOR USE AND STORAGE

Store in closed original packings, protected from heat, in a temperate area (possible temperatures of storage : 0 to + 40°C). If possible bring the product back to about 20°C before application. Always shake well before use.

For more information regarding the danger of the product, please consult the product safety data sheet according to local regulation.

For professional use only.

This technical data sheet replaces and cancels the previous one.

The above details have been compiled to the best of our knowledge. They have, however, an indicative value only and we therefore make no warranties and assume no liability in connection with any use of this information, particularly if a third party's rights are affected by the use of our products. The above information has been compiled based upon tests carried out by SOCOMORE. All data is subject to change as Socomore deems appropriate. The data given is not intended to substitute for any testing you must conduct in order to determine the suitability of the product for your particular purposes. Please check your local legislation applicable to the use of this product. Should you need any further information please contact us.